



Fuse-link, high speed, 160 A, AC 690 V, size 000, 24 x 36 x 96 mm, aR, IEC



170M1469

| General specifications | | |
|------------------------|--|---|
| Product name | | Eaton Bussmann series high speed square body fuse |
| Part no. | | 170M1469 |
| EAN | | 5027590441063 |
| Product Length/Depth | | 140 millimetre |
| Product height | | 40 millimetre |
| Product width | | 102 millimetre |
| Product weight | | 137.4 gram |
| Compliances | | Contact factory RoHS Compliant |
| Product Tradename | | None |
| Product Type | | High speed square body fuse |
| Product Sub Type | | None |
| Electrical data | | |
| Amperage Rating | | 160 A |
| Voltage rating | | 690 V |
| Interrupt rating | | 200 kAIC |
| Class | | Class aR |
| Product specifications | | |
| Application | | semiconductor protection |
| Fuse type | | Bolted tag |
| Fuse indicator | | None |
| Fuse size | | 000 |

Technical data ETIM 9.0

| | | |
|--|----|---|
| Circuit breakers and fuses (EG000020) / HRC fuse (EC004556) | | |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss13-27-14-20-90 [BAB264016]) | | |
| Fuse system according to IEC 60269 | | Other |
| Fuse construction type according to IEC 60269 | | 000 |
| Type of current | | AC |
| Rated voltage AC | V | 690 |
| Rated voltage DC | V | |
| Rated current | A | 160 |
| Utilization category | | aR (accompanied semiconductor protection) |
| Breaking capacity | kA | 200 |
| Colour code | | None |
| Type of fuse status indicator | | None |
| Power loss at rated current | W | 32 |
| Mounting holes | | M8 |
| Centre-to-centre distance of connections | mm | 73.8 |